PRODUCT INFORMATION

Double ledger futuro U-support with reduced construction height

Double Ledger U-Support in different lengths from 1.40 to 3.07 m. With a reduced construction height to about 7,6 cm.

Code	Description	Dimensions (cm)	Weight
5F00307414	Double ledger futuro, U-support	L140	8,7 kg
5F00307415	Double ledger futuro, U-support	L157	9,9 kg
5F00307420	Double ledger futuro, U-support	L207	13,2 kg
5F00307425	Double ledger futuro, U-support	L257	16,6 kg
5F00307430	Double ledger futuro, U-support	L307	19,9 kg

ADVANTAGES

- Less restriction of the clearance height during assembling in case of lying on top of each other.
- Despite the reduced construction height, a practical load-bearing capacity is achieved.



Load capacity of futuro double ledgers, U-support (reduced construction height 7,6 cm)

Ledger length (m)	q (kN/m)	Deck length (m)	Deck-to- deck ledger q (kN/m²)	Load class	Ledger-to- deck ledger q (kN/m²)	Load class
		3.07	5.0	5	10.3	6
		2.57	6.0	5	12.3	6
1.40	16.1	2.07	7.5	5	15.3	6
		1.57	10.0	6	20.3	6
1.57	14.3	3.07	4.4	4	9.1	6
		2.57	5.3	5	10.9	6
		2.07	6.7	5	13.6	6
		1.57	8.9	6	18.0	6
2.07	9.8	3.07	3.0	3	6.2	5
		2.57	3.6	4	7.4	5
		2.07	4.5	4	9.2	6
		1.57	6.0	5	12.3	6
2.57	6.0	3.07	1.7	2	3.7	4
		2.57	2.1	3	4.5	4
		2.07	2.7	3	5.6	5
		1.57	3.6	4	7.4	5
3.07	4.3	3.07	1.2	1	2.6	3
		2.57	1.4	2	3.1	3
		2.07	1.8	2	3.9	4
		1.57	2.5	3	5.2	4



*approval in preparation



ALTRAD PLETTAC ASSCO GMBH Adam-Opel Straße 7 – 58840 Plettenberg, Germany Tel.: +49 2391 815-01 – E-Mail: info@plettac-assco.de www.plettac-assco.de